



**Site Agent:-**  
  
Morrison Supervisor

All Traffic Management will be in accordance with Safety at streetworks and roadworks Code of Practice 2013

Dual carriageways (lane closures) restricted to 40mph or less  
 Minimum sitting distance of first sign in advance of lead in taper 300mtrs  
 Minimum taper length calculated dependant on width of hazard at a rate of 1:25 with cone spacing of 3mtrs  
 Single carriageway restricted to 30mph or less  
 Minimum sitting distance of first sign in advance of lead in taper 20mtrs  
 (lane closures) Minimum taper length calculated dependant on width of hazard at a rate of 1:13

All lead in tapers used with temp traffic lights / stop go boards / priority boards will be at 45 degrees from kerb line at 1.2 metre spacing  
 Unmarked running lanes will be maintained at 3.5 metres.  
 Unmarked walkways will be maintained at 1.5 metres or wider  
 DO NOT SCALE FROM THIS DRAWING

**DRAWN:-** Kevin McQueen  
 Kevin.mcqueen@morrisonws.com  
**REF:** KM091023-2  
**SCALE:** N/A  
**Checked :** John Davidson

**SITE ADDRESS:-**  
 1872  
 ZHEADN02  
 Cotswold Crescent  
 Haynes Road  
 Marston  
 Oxford  
 OX3 0SF

**Key**

- Works area
- Safety zone
- 1m Road cones
- Aspect of sign view
- Barrier/Fencing
- Traffic Signal

Parking Not Bays	N
Parking Bays	N
Pedestrian Switch out	N
Junction Switch Out	N
Bus Stop	N
Zebra Crossing Bag Off	N
Disabled/Taxi/Loading Bay	N
Bus Lane Closure/Suspend	N

**FREE PARKING**  
  
YES

**SIGNS TO BE PLACE ON FENCING/BARRIER**

we're making improvements

We expect to finish on

END DATE

Your ref: BB

08003169800

thameswater.co.uk/yourarea

Permit number: PERMIT

Contractor:

Thank you for your patience

While we work to keep your services as clear as possible

We're making pipes smarter

With new technology to help detect leaks and low pressure earlier

Here until

We'll finish sooner if we can

OR

We're fixing pipes

So we can always bring you world-class tap water

